

ALL NEW ISUZU PUV

The Future of Public Transportation is Here

Meet the new faces of the PUVs now made modern, efficient, and more reliable.



CENTRO
MANUFACTURING CORPORATION




santarosa



ALMAZORA
Motors Corporation

ISUZU PUV SEAT DESIGN



Class 2



Class 3

ISUZU
Your responsible partner

ISUZU PUV ACCESSORY

*MAY VARY DEPENDING ON PREFERRED BODY BUILDER



CCTV



Handle and Grip




PVD Seats



Stereo



Rear Camera



Front Camera



Fire Extinguisher

PARTNERED AIRCON SUPPLIERS



NLR77 PUV SPECIFICATIONS

BODY SUPPLIER	ALMAZORA		CENTRO		SANTA ROSA	
PUV CLASS	2	3	2	3	2	3
Seat Configuration	Side Facing	Front Facing	Side Facing	Front Facing	Side Facing	Front Facing
Seating Capacity	20 + 1	23 + 1	22 + 1	20 + 1	20 + 1	23 + 1
DIMENSIONS						
Overall Length (mm)	6,122	6,460	6,126	6,461	6,100	6,420
Overall Width (mm)	1,825		1,777		1,815	
Overall Height (mm)	2,600 (approx.)					
Wheelbase (mm)	3,345					
BODY CONSTRUCTION						
Structural Frame	Rectangular-Square with Channel Sections		GA Sheet and Bended MS Plate		Skeleton Type Frame w/ Rectangular Tubings	
Panels	Fiberglass Roof & Galvanneal Sides		GA Sheet		Side: Galvanneal Molded FRP w/ ABS Plastic; Roof: Aluminum Composite	
Body Color	Arc White					
INTERIOR DETAILS						
Side Window	Fixed Window Type w/ Sliding Upper Glass				Fixed Window Type w/ Emergency Exit Glass	
Service Door	Folding Type - Electric Door Closer					
Seats and Materials	Fixed Type Seats w/ Backrest (Fiberglass)	Bench Type Seats w/ Backrest (Fabric-Leatherette Upholstery)			Bench Type Seats w/ Backrest (Synthetic Leather w/ Cushion and Slab Foam)	
Rear Window	Fixed Type (Tempered Glass)					
Main Flooring	Phenolic Board with Vinyl Matting				Marine Plywood and PVC Non-Slip Matting	
WEIGHT						
Gross Vehicle Weight (GVW) (kg)	4,800 kg					
DIMENSIONS						
Overall Length X Width (mm)	6,019 mm x 1,770 mm					
Wheelbase (mm)	3,345 mm					
Front Overhang / Rear Overhang (mm)	1,015 mm / 1,570 mm					
ENGINE						
Model	4JH1-TC					
Type	4-Cylinder, Turbo-Intercooler, Common Rail Direct Injection, Blue Power Diesel Engine					
Emission Standard	Euro IV					
Displacement (cc)	2,999 cc					
Maximum Output (rpm)	106 PS / 3,200 rpm					
Maximum Torque (rpm)	230 N-m / 1,400 - 3,200 rpm					
Fuel Tank Capacity (L)	75 Liters					
TRANSMISSION						
Model	MSB5S					
Type	5-Speed Manual Transmission					
Final Gear Ratio	5.125					
TIRE & WHEEL						
Tire	7.50-15-14PR					
ELECTRICAL						
Alternator	12V - 135A					
Battery	95D31L x 1					
BRAKE						
Service	Drum Type, Vacuum					
Parking	Center Brake					
SUSPENSION						
Front and Rear	Multi-Leaf Spring					
CONVENIENCE						
Audio	Tuner Radio w/ AUX & USB					

Dealership:

Isuzu Philippines Corporation reserves the right to change features and specifications without prior notice. Details, descriptions, and illustrations are for informational purposes only and may vary from actual units.

Printed: January 2021

ISUZU PHILIPPINES CORPORATION

114 Technology Ave., Phase II, Laguna Technopark, Biñan, Laguna, 4024
Trunkline (049) 541-0224 / (02) 757-8070
Email: customer-relations@isuzuphil.com